C610 DM Specifications

OKI



Print your medical imaging in HD colour with integrated DICOM A4 printers

OKI is a leader in printing innovation, providing organisations with High Definition colour printing devices based on digital LED technology, and now our sophisticated range of printers integrate seamlessly with your clinical systems using DICOM.

A first in medical imaging and printing

This is a first in digital printer technology, combining the cost effectiveness and high quality output of an LED printer with embedded DICOM software, allowing you to print directly from medical equipment without the use of conversion software or external print servers. You no longer need to settle for expensive printing on specialist media and devices.

With the C610 DM you can now print your medical imaging cost effectively on standard media formats in vibrant, HD colour and in sizes up to A4. From nuclear medicine (2D Scintigraphy and 3D SPECT tomography) to ultrasounds, these images can now be easily printed for your own non-diagnostic use or to provide a copy for your patients and clients to take away with them.

Reduce your costs and improve your printing

The C610 DM is not only perfect for your medical imaging printing, it can also be used for your standard office printing, from patient letters and forms to medical reports, allowing you to choose one machine that answers all the needs of your organisation, cutting down on the number of devices and consumables used.

The C610 DM is based on our existing, award winning printers, offering the same reliability, ease of use, low total cost of ownership, media flexibility and high quality output, with the additional benefit of embedded DICOM technology. Through system integration, the use of energy efficient equipment, standard printer consumables and a three year on-site warranty, the C610 DM offers considerable savings for your day-to-day printing needs.

See it clearer with OKI

Talking directly with your medical imaging equipment, the C610 DM presents many opportunities for printing high quality, nondiagnostic images in HD mono and colour on a wide range of media. The significantly reduced costs of printing using the C610 DM, compared with traditional DICOM printing technologies, allows medical establishments to change their approach to printing. Imagine the possibilities; offer mothers-to-be A4 ultrasound scans or keep sharp and clear nondiagnostic images in patients' records, and all at a very low cost. In fact, the same cost of printing as standard office documents.

- Fully integrated DICOM print server
- Up to 2 simultaneous imaging equipment connections
- Recommended usage Nuclear medicine, ultrasound
- High quality non-diagnostic mono and colour printing of medical images
- No additional external hardware or software required
- Handles media from A6 to A4 wide 1200mm banners, from 64 to 250gsm
- Three year on-site warranty (product to be registered within 30 days of purchase)



C610 DM - Colour and Mono DICOM Embedded Printer

| OVERVIEW | | |
|-----------------------------|--|--|
| Description | The C610 DM is our most compact DICOM imager. Primarly designed for Ultrasonography, it can of course be connected to other DICOM print SCU compliant modalities | |
| Imaging Technology | CMYK toner based engine with tandem technology. Light sources are LED arrays @ 600 ppi with multi level capability | |
| Network | 10/100 Base TX (RJ45) interface | |
| GENERAL FEATURES | | |
| Print Format - Paper weight | A4 - 64 to 250 gsm | |
| Dimensions (HxWxD) | 340 x 435 x 546mm | |
| Weight | 26kg | |
| DICOM Server Features | | |
| Capability | DICOM 3.0 Print SCP | |
| Maximum number of AET | 25 | |
| Max # calling modalities | No limitations | |
| Maximum connections | 2 simultaneous | |
| Dicom Server interface | Integrated web server | |
| Log | Extented log capability in case of troubleshooting | |
| LUT support | identity, reverse, lin-od | |
| Image generation | Specific color rendering optimized for medical images | |

 Image generation
 Specific color rendering optimized for medical images

 Graphical Header
 Capability to add a graphical header on each printout

AET DEPENDENT FEATURES

| AET Name | Print SCP Application Entity Title (AET) | |
|-----------------------------------|--|--|
| Printer Tray | Use prefered paper for your medical prints | |
| Сору | Send one, print what you need | |
| Border Density | Value from Black, White or Client | |
| Empty image Density | Value from Black, White or Client | |
| Replace Header by Logo | Use a graphical header instead of text for enhenced communication on the printouts | |
| Header | Enter text that will print on top of page or select Logo | |
| Footer | Edit the text on page bottom | |
| Contrast | t Add or remove contrast on the printouts | |
| Brightness | Add or remove brightness on the printouts | |
| Hi Quality Glossy Black | Print your greyscale images using best composite rendering | |
| Cyan, Magenta and Yellow Gamma | | |
| Smoothing | Prompts C610 to use or not adjustable Sharpen filter to print | |
| Polarity | Force image polarity inversion if needed | |

| Consumables (Order Numbers) | | |
|------------------------------------|---|--|
| Toner cartridges* (6,000 pages) | Cyan: 44315307; Magenta: 44315306; Yellow: 44315305 | |
| Toner cartridges* (8,000 pages) | Black: 44315308 | |
| Image drum** (20,000 pages) | Cyan: 44315107; Magenta: 44315106; Yellow: 44315105; Black: 44315108 | |
| Transfer Belt (60,000 pages) | 44341902 | |
| Fuser Unit (60,000 pages) | 44289103 | |

OFFICE USAGE FEATURES

C610 DM inherits all features of standard product Please refer to C610 specsheet available on OKI websites

DICOM INTERFACE

On embedded web server Full configuration of the server features, log viewing

| Print SCP AET Configuration | | |
|------------------------------|--|--|
| AET Name | OKI | |
| Activate Max Dicom Log | | |
| | | |
| Use US format paper | AUTO | |
| Printer Tray | | |
| Сору | CLIENT | |
| Border Density | CLIENT | |
| Empty Image Density | CLIENT | |
| | | |
| Replace Header by Logo | | |
| | Using Logo as Header reduce image printing area | |
| Header | | |
| Footer | DICOM Embedded Printer - Not for diagnostic use - C | |
| | Editing this original statement footer is full responsability of the user. | |
| Contrast | 0 | |
| Brightness | 0 | |
| Hi Quality Glossy Black Mode | | |
| Cyan gamma (0.01 to 2.90) | 0.85 | |
| Magenta gamma (0.01 to 2.90) | 0.89 | |
| Yellow gamma (0.01 to 2.90) | 0.82 | |
| | | |
| Smoothing Filter | CLIENT | |
| Smoothing Level | LOW | |
| | | |
| Polarity | CLIENT | |

Accessories (Order Numbers)

| 2nd paper tray | 44274502 |
|----------------|----------|
| 3rd paper tray | 44274502 |
| Duplex | 01272601 |
| Cabinet | 01219302 |



*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with 2,000 A4 pages. Medical printing strongly alter these values. **Drum: A4 pages average life.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

3 Year On-site Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit www.oki.co.uk/wARRANTY. Without registration, the standard pan-European 1 year warranty applies.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199 WWW.0KIEUROPE.COM



C711 DM Specifications





Print your medical imaging in HD colour with integrated DICOM A4 printers

OKI is a leader in printing innovation, providing organisations with High Definition colour printing devices based on digital LED technology, and now our sophisticated range of printers integrate seamlessly with your clinical systems using DICOM.

A first in medical imaging and printing

This is a first in digital printer technology, combining the cost effectiveness and high quality output of an LED printer with embedded DICOM software, allowing you to print directly from medical equipment without the use of conversion software or external print servers. You no longer need to settle for expensive printing on specialist media and devices.

With the C711 DM you can now print your medical imaging cost effectively on standard media formats in vibrant, HD colour and in sizes up to A4. From x-rays (eg dental, veterinary, hospital, clinic) to nuclear medicine, scans (eg MRI, CT) and ultrasounds, these images can now be easily printed for your own non-diagnostic use or to provide a copy for your patients and clients to take away with them.

Reduce your costs and improve your printing

The C711 DM is not only perfect for your medical imaging printing, it can also be used for your standard office printing, from patient letters and forms to medical reports, allowing you to choose one machine that answers all the needs of your organisation, cutting down on the number of devices and consumables used.

The C711 DM is based on our existing, award winning printers, offering the same reliability, ease of use, low total cost of ownership, media flexibility and high quality output, with the additional benefit of embedded DICOM technology. Through system integration, the use of energy efficient equipment, standard printer consumables and a three year on-site warranty, the C711 DM offers considerable savings for your day-to-day printing needs.

See it clearer with OKI

Talking directly with your medical imaging equipment, the C711 DM presents many opportunities for printing high quality, nondiagnostic images in HD mono and colour on a wide range of media. The significantly reduced costs of printing using the C711 DM, compared with traditional DICOM printing technologies, allows medical establishments to change their approach to printing. Imagine the possibilities; print MRI scans in colour, offer mothers-to-be A4 ultrasound scans or keep sharp and clear non-diagnostic images in patients' records, and all at a very low cost. In fact, the same cost of printing as standard office documents.

- Fully integrated DICOM print server
- Up to 3 simultaneous imaging equipment connections
- Recommended usage Nuclear medicine, ultrasound, MRI/CT scans, x-rays
- High quality non-diagnostic mono and colour printing of medical images
- No additional external hardware or software required
- Handles media from A6 to A4 wide 1200mm banners, from 64 to 250gsm
- Three year on-site warranty (product to be registered within 30 days of purchase)



C711 DM - Colour and Mono DICOM Embedded Printer

| The C711 DM is our most capable A4 DICOM imager. With high yeald consumables, it can serve different modalities as X-ray, Utrasound, PX | |
|---|--|
| CMYK toner based engine with tandem technology. Light sources are LED arrays @ 600 dpi with multi level capability | |
| 10/100 Base TX (RJ45) interface | |
| | |
| A4 - 64 to 250 gsm | |
| 389 x 435 x 546mm | |
| 28kg | |
| | |
| DICOM 3.0 Print SCP | |
| 25 | |
| No limitations | |
| 3 simultaneous | |
| Integrated web server | |
| Extented log capability in case of troubleshooting | |
| identity, reverse, lin-od | |
| Specific color and mono rendering optimized for medical images | |
| Capability to add a graphical header on each printout | |
| | |
| Print SCP Application Entity Title (AET) | |
| Use prefered paper for your medical prints | |
| Send one, print what you need | |
| Value from Black, White or Client | |
| Value from Black, White or Client | |
| Use a graphical header instead of text for enhenced communication on the printouts | |
| Enter text that will print on top of page or select Logo | |
| F Edit the text on page bottom | |
| Add or remove contrast on the printouts | |
| Add or remove brightness on the printouts | |
| Print your greyscale images using best composite rendering | |
| Range from 0.01 to 2.90 by step of 0.01. Values lower than 1.0 will lighten, values higher than 1.00 will darken the image | |
| | |
| | |

| Consumables (Order Numbers) | |
|-------------------------------------|--|
| Toner cartridges* (11,500 pages) | Cyan: 44318607; Magenta: 44318606; Yellow: 44318605 |
| Toner cartridges* (11,000 pages) | Black: 44318608 |
| Image drum** (20,000 pages) | Cyan: 44318507; Magenta: 44318506; Yellow: 44318505; Black: 44318508 |
| Transfer Belt (60,000 pages) | 44341902 |
| Fuser Unit | |

(60,000 pages) 44289103

OFFICE USAGE FEATURES

C711 DM inherits all features of standard product Please refer to C711 specsheet available on OKI websites

DICOM INTERFACE

On embedded web server Full configuration of the server features, log viewing

| Print SCP AET Configuration | | |
|--|--|--|
| AET Name | OKI | |
| Activate Max Dicom Log | | |
| Use US format paper | | |
| Printer Tray | AUTO | |
| Сору | | |
| 60p) | oberti - | |
| Border Density | CLIENT - | |
| Empty Image Density | CLIENT - | |
| | | |
| Replace Header by Logo | | |
| | Using Logo as Header reduce image printing area | |
| Header | | |
| Footer | DICOM Embedded Printer - Not for diagnostic use - | |
| | Editing this original statement footer is full responsability of the user. | |
| Contrast | - | |
| | | |
| Brightness | 0 | |
| Hi Quality Glossy Black Mode | | |
| Black gamma (0.01 to 2.90) | 0.7 | |
| Cyan gamma (0.01 to 2.90) | 0.85 | |
| Magenta gamma (0.01 to 2.90) | 0.89 | |
| Yellow gamma (0.01 to 2.90) | 0.82 | |
| u () () () () () () () () () (| | |
| Smoothing Filter | CLIENT - | |
| Smoothing Level | LOW - | |
| Polarity | CLIENT | |

| Accessories | (Order | NUMBERS) |) |
|-------------|--------|----------|---|
| | | | |

| 2nd paper tray | 44274502 |
|----------------|----------|
| 3rd paper tray | 44274502 |
| Duplex | 01272601 |
| Cabinet | 01219302 |
| cabilier | 0121/502 |



*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with toner for 4,000 pages. Medical printing strongly alter these values. **Drum: Average number of A4 pages printed.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

3 Year On-site Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit **www.oki.co.uk/warranty**. Without registration, the standard pan-European 1 year warranty applies.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199 WWW.0KIEUROPE.COM



C831 DM Specifications

OKI



Print your medical imaging in HD colour with integrated DICOM A4/A3 printers

OKI is a leader in printing innovation, providing organisations with High Definition colour printing devices based on digital LED technology, and now our sophisticated range of printers integrate seamlessly with your clinical systems using DICOM.

A first in medical imaging and printing

This is a first in digital printer technology, combining the cost effectiveness and high quality output of an LED printer with embedded DICOM software, allowing you to print directly from medical equipment without the use of conversion software or external print servers. You no longer need to settle for expensive printing on specialist media and devices.

With the C831 DM you can now print your medical imaging cost effectively on standard media formats in vibrant, HD colour and in sizes up to A3. From nuclear medicine to scans (eg MRI, CT) and ultrasounds, these images can now be easily printed for your own non-diagnostic use or to provide a copy for your patients and clients to take away with them.

Reduce your costs and improve your printing

The C831 DM is not only perfect for your medical imaging printing, it can also be used for your standard office printing, from patient letters and forms to medical reports, allowing you to choose one machine that answers all the needs of your organisation, cutting down on the number of devices and consumables used.

The C831 DM is based on our existing, award winning printers, offering the same reliability, ease of use, low total cost of ownership, media flexibility and high quality output, with the additional benefit of embedded DICOM technology. Through system integration, the use of energy efficient equipment, standard printer consumables and a three year on-site warranty, the C831 DM offers considerable savings for your day-to-day printing needs.

See it clearer with OKI

Talking directly with your medical imaging equipment, the C831 DM presents many opportunities for printing high quality, nondiagnostic images in HD mono and colour on a wide range of media. The significantly reduced costs of printing using the C831 DM, compared with traditional DICOM printing technologies, allows medical establishments to change their approach to printing. Imagine the possibilities; print MRI scans in colour, offer mothers-to-be A4 or A3 ultrasound scans or keep sharp and clear non-diagnostic images in patients' records, and all at a very low cost. In fact, the same cost of printing as standard office documents.

- Fully integrated DICOM print server
- Up to 3 simultaneous imaging equipment connections
- Recommended usage Nuclear medicine, ultrasound, MRI/CT scans
- High quality non-diagnostic mono and colour printing of medical images
- No additional external hardware or software required
- Handles media from A6 to A3 wide 1200mm banners, from 64 to 256gsm
- Three year on-site warranty (product to be registered within 30 days of purchase)



C831 DM - Colour and Mono DICOM Embedded Printer

| Description | The C831 DM is a very small footprint A4/A3 DICOM imager. |
|---|---|
| Description | Perfect for nuclear medecine, ultrasound, CT, MRI |
| Imaging Technology | CMYK toner based engine with tandem technology. Light sources are LED arrays @ 600 dpi with multi level capability |
| Network | 10/100 Base TX (RJ45) interface |
| | |
| eneral Features | |
| Print Format - Paper weight | A4 and A3 - 64 to 256gsm |
| Dimensions (HxWxD) | 360 x 449 x 552mm |
| Weight | 37kg |
| OICOM SERVER FEATURES | |
| | DICOM 3.0 Print SCP |
| Capability Maximum number of AET | 25 |
| | |
| Max # calling modalities Maximum connections | No limitations 3 simultaneous |
| Dicom Server interface | Integrated web server |
| | |
| Log | Extented log capability in case of troubleshooting |
| LUT support | identity, reverse, lin-od |
| Image generation | Specific color and mono rendering optimized for medical images |
| Graphical Header | Capability to add a graphical header on each printout |
| | |
| ET DEPENDENT FEATURES | |
| AET Name | Print SCP Application Entity Title (AET) |
| Printer Tray | Use prefered paper for your medical prints |
| Сору | Send one, print what you need |
| Page Format | Force the printout on the selected format |
| Border Density | Value from Black, White or Client |
| Empty image Density | Value from Black, White or Client |
| Replace Header By Logo | Use a graphical header instead of text for enhenced communication on the printouts |
| Header | Enter text that will print on top of page if Logo isn't used |
| Footer | Edit the text on page bottom |
| Contrast | Add or remove contrast on the printouts |
| Brightness | Add or remove brightness on the printouts |
| Hi Quality Glossy Black | Print your greyscale images using best composite rendering |
| Cyan, Magenta and Yellow Gamma | Range from 0.01 to 2.90 by step of 0.01. Values lower than 1.00 will lighten, values higher than 1.00 will darken the image |
| Smoothing | Prompts C831 to use or not adjustable Sharpen filter to print |
| | |
| Polarity | Force image polarity inversion if needed |

| Consumables (Order Numbers) | |
|-------------------------------------|---|
| Toner cartridges* (10,000 pages) | Cyan: 44844507; Magenta: 44844506; Yellow: 44844505; Black: 44844508 |
| Image drum** (30,000 pages) | Cyan: 44844407; Magenta: 44844406; Yellow: 44844405; Black: 44844408 |
| Transfer Belt (80,000 pages) | 44846204 |
| Fuser Unit (100,000 pages) | 44848805 |
| OFFICE USAGE FEATURES | |

C831 DM inherits all features of standard product Please refer to C831 specsheet available on OKI websites

DICOM INTERFACE

On embedded web server Full configuration of the server features, log viewing

| Print SCP AET Configuration | | | |
|-------------------------------|--|--|--|
| AET Name | OKI | | |
| Activate Max Dicom Log | | | |
| | | | |
| Use US format paper | | | |
| Printer Tray | AUTO - | | |
| Сору | CLIENT - | | |
| Page Format | CLIENT - | | |
| | | | |
| Border Density | CLIENT - | | |
| Empty Image Density | CLIENT - | | |
| | | | |
| Replace Header by Logo | | | |
| | Using Logo as Header reduce image printing area | | |
| Header | | | |
| Footer | DICOM Embedded Printer - Not for diagnostic use - | | |
| Contrast | Editing this original statement footer is full responsability of the user. | | |
| Brightness | 0 • | | |
| Digitiless | 0 • | | |
| Hi Quality Glossy Black Mode | V | | |
| Cyan gamma (0.01 to 2.90) | 0.85 | | |
| Magenta gamma (0.01 to 2.00) | 0.89 | | |
| Yellow gamma (0.01 to 2.90) | 0.82 | | |
| Tellow gallina (0.01 to 2.90) | 0.02 | | |
| Smoothing Filter | CLIENT | | |
| Smoothing Level | | | |
| Smoothing Level | | | |
| Polarity | CLIENT - | | |





*Toners: A4 pages yield compliant with ISO/ISC 19798. Printer shipped with toner for 2,500 A4 pages yield compliant with ISO/ISC 19798. Medical printing strongly alter these values. **Drum: Average number of A4 pages printed.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

3 Year On-site Warranty

Duplex 44717603

Cabinet 01321101

2nd/3rd/4th paper tray 44713903

Accessories (Order Numbers)

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit **www.oki.co.uk/warranty**. Without registration, the standard pan-European 1 year warranty applies.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199 WWW.0KIEUROPE.COM



©2014 Oki Europe Ltd. Oki Europe Ltd. is part of the OKI Electric group of companies. Version 3.0 11/2014. Specification subject to change without notice. All trademarks acknowledged. *DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.

C910 DM Specifications

OKI



Print your medical imaging in HD colour with integrated DICOM A4 / A3 printers

OKI is a leader in printing innovation, providing organisations with High Definition colour printing devices based on digital LED technology, and now our sophisticated range of printers integrate seamlessly with your clinical systems using DICOM.

A first in medical imaging and printing

This is a first in digital printer technology, combining the cost effectiveness and high quality output of an LED printer with embedded DICOM software, allowing you to print directly from medical equipment without the use of conversion software or external print servers. You no longer need to settle for expensive printing on specialist media and devices.

With the C910 DM you can now print your medical imaging cost effectively on standard media formats in vibrant, HD colour and in sizes up to A3+. From x-rays (eg dental, veterinary, hospital, clinic) to nuclear medicine, scans (eg MRI, CT) and ultrasounds, these images can now be easily printed for your own non-diagnostic use or to provide a copy for your patients and clients to take away with them.

Reduce your costs and improve your printing

The C910 DM is not only perfect for your medical imaging printing, it can also be used for your standard office printing, from patient letters and forms to medical reports, allowing you to choose one machine that answers all the needs of your organisation, cutting down on the number of devices and consumables used.

The C910 DM is based on our existing, award winning printers, offering the same reliability, ease of use, low total cost of ownership, media flexibility and high quality output, with the additional benefit of embedded DICOM technology. Through system integration, the use of energy efficient equipment, standard printer consumables and a three year on-site warranty, the C910 DM offers considerable savings for your day-to-day printing needs.

See it clearer with OKI

Talking directly with your medical imaging equipment, the C910 DM presents many opportunities for printing high quality, nondiagnostic images in HD mono and colour on a wide range of media. The significantly reduced costs of printing using the C910 DM, compared with traditional DICOM printing technologies, allows medical establishments to change their approach to printing. Imagine the possibilities; print MRI scans in colour, offer mothers-to-be A4 or A3 ultrasound scans or keep sharp and clear non-diagnostic images in patients' records, and all at a very low cost. In fact, the same cost of printing as standard office documents.

- Fully integrated DICOM print server
- Up to 5 simultaneous imaging equipment connections
- Recommended usage Nuclear medicine, ultrasound, MRI/CT scans, x-rays
- High quality non-diagnostic mono and colour printing of medical images
- No additional external hardware or software required
- Handles media from A6 to A3+ and A3 wide 1200mm banners, from 64 to 300gsm
- Three year on-site warranty (product to be registered within 30 days of purchase)



C910 DM - Colour and Mono DICOM Embedded Printer

| Overview | | CONSUMABLES (ORDER NUM | BERS) |
|--|--|--|---|
| Description | Initially designed for graphic application, the C910 DM has been heavily optimized for DICOM reproduction needs, resulting in very high quality output for all medical imaging centers needs. | Toner cartridges* (15,000 pages) | Cyan: 44036023; Magenta: 44036022; Yellow: 44036021; Black: 44036024 |
| | | Image drum** (20,000 pages) | Cyan: 44035519; Magenta: 44035518; Yellow: 44035517; Black: 44035520 |
| Imaging Technology | CMYK toner based engine with tandem technology. Light sources are LED arrays @ 600 dpi with multi level capability | Transfer Belt (100,000 pages) | 42931603 |
| | 10/100/1000 Base TX (RJ45) interface | Fuser Unit (100,000 pages) | 42931703 |
| GENERAL FEATURES | 44 442 444 200 | Waste Toner Box | 42869403 |
| Print Format - Paper weight | | (30,000 pages) | 42007405 |
| Dimensions (HxWxD) | 471 x 654.5 x 623mm | Finisher Staples (15,000 staples) | 42937603 |
| Weight | /6kg | (15,000 stapies) | |
| DICOM Server Features | | OFFICE USAGE FEATURES | · · · · · · · · · · · · · · · · · · · |
| Capability | DICOM 3.0 Print SCP | C910 DM inherits all features of standard product | Please refer to C910 specsheet available on OKI websites |
| Maximum number of AET | 25 | reatures of standard product | |
| Max # calling modalities | No limitations | DICOM INTERFACE | |
| Maximum connections | 5 simultaneous | On embedded web server | Full configuration of the server features, log viewing |
| Dicom Server interface | Integrated web server | | Print SCP AET Configuration |
| Log | Extented log capability in case of troubleshooting | AET Name | |
| LUT support | identity, reverse, lin-od | Activate Max Dicom Log | |
| Image generation | Specific color and mono rendering optimized for medical images | Use US format paper Printer Tray | AUTO - |
| Graphical Header | Capability to add a graphical header on each printout | Copy Page Format | CLIENT - CLIENT - |
| AET DEPENDENT FEATURES | | Border Density Empty Image Density | CLIENT - CLIENT - |
| AET Name | Print SCP Application Entity Title (AET) | | CLENT • |
| Printer Tray | Use prefered paper for your medical prints | Replace Header by Logo | Using Logo as Header reduce image printing area |
| Сору | Send one, print what you need | Header | |
| Page Format | Force the printout on the selected format | Footer | DICOM Embedded Printer - Not for diagnostic use - Editing this original statement footer is full responsebility of the user. |
| Border Density | Value from Black, White or Client | Contrast Brightness | |
| Empty image Density | Value from Black, White or Client | Diginiess | U V |
| Replace Header By Logo | Use a graphical header instead of text for enhenced communication on the printouts | Hi Quality Glossy Black Mode Black gamma (0.01 to 2.90) | 10 |
| Header | Enter text that will print on top of page if Logo isn't used | Cyan gamma (0.01 to 2.90) Magenta gamma (0.01 to 2.90) | 1.0 |
| Footer | Edit the text on page bottom | Yellow gamma (0.01 to 2.90) | 1.0 |
| Contrast | Add or remove contrast on the printouts | Activate Halftoning | |
| Brightness | Add or remove brightness on the printouts | Smoothing Filter | CLIENT - |
| Hi Quality Glossy Black | Print your greyscale images using best composite rendering | Smoothing Level | LOW - |
| Greyscale, Cyan, Magenta and Yellow Gamma | Range from 0.01 to 2.90 by step of 0.01. Values lower than 1.00 will lighten, values higher than 1.00 will darken the image | | |
| Activate Halftoning | For advanced user only, allow printer screening selection | | |
| Smoothing | Prompts C910 to use or not adjustable Sharpen filter to print | | - 1907 est est |
| | | | |

Polarity Force image polarity inversion if needed

Accessories (Order Numbers)

| 2nd/3rd paper tray | 42831303 |
|----------------------|----------|
| Duplex | 42797203 |
| High Capacity Feeder | 42831503 |
| Cabinet | 09004256 |

*Toner: Number of A4 pages @ 5% coverage. Printer shipped with toner for 7,500 pages @ 5%. Medical printing strongly alter these values. **Drum: Average number of A4 pages printed.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

3 Year On-site Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit www.oki.co.uk/warRANTY. Without registration, the standard pan-European 1 year warranty applies.

.....

- 1

1

- 1

- 1

ОКІ ЕUROPE LTD. Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199 WWW.OKIEUROPE.COM

